


SPECIFICATION SHEET

Imperial [IP] Dimensions

Metric (SI) in Parentheses

## SINGLE DUCT AIR TERMINAL - WITH ELECTRIC REHEAT ANALOG ELECTRONIC CONTROLS ET - CONTROL OPTION

CARNES COMPANY 448 S. Main St., P. O. Box 930040, Verona, WI 53593-0040 Phone: (608)845-6411 Fax: (608)845-6504 www.carnes.com




## SEQUENCE OF OPERATION

ON A CALL FOR COOLING, AIRFLOW WILL INCREASE AS THE DAMPER OPENS TOWARDS THE MAXIMUM CFM SETTING TO SATISFY ROOM SET-POINT.

ON A CALL FOR HEATING, AIRFLOW WILL DECREASE AS THE DAMPER CLOSES TOWARDS THE MINIMUM CFM SETTING TO SATISFY ROOM SET-POINT.

WITH A FURTHER CALL FOR HEAT, AIRFLOW IS AT MINIMUM CFM AND HEATING STAGE ONE (C1) IS ENERGIZED AT THE HEATING SET-POINT. IF ADDITIONAL HEAT IS REQUIRED, THE SECOND (C2) AND THIRD (C3) STAGES OF HEAT ARE ENERGIZED. HEATING STAGES ARE DEENERGIZED AS ROOM TEMPERATURE INCREASES. AIRFLOW WILL INCREASE TO SATISFY ROOM SET-POINT.



COPYRIGHT © 2012 CARNES COMPANY ALL RIGHTS RESERVED

SUPERSEDES 20165-B

20165-C